COUPLEMATE BEARING CONFIGURATION

COUPLEMATE CALLER PARTS

BEARINGS	COMBINATION	INNER B/CONE	OUTER B/CONE	INNER I/D	INNER O/D	OUTER I/D	OUTER O/D	SEAL	SEAL O/D	SEAL I/D
<u>CM489</u>	LM	LM67048/10	<u>LM11949/10</u>	31.75mm	59.10mm	19.05mm	45.20mm	<u>491015</u>	59.10mm	37.50mm
<u>CM489M</u>	LM MARINE	LM67048/10	LM11949/10	31.75mm	59.10mm	19.05mm	45.20mm	<u>492020</u>	59.10mm	37.50mm
<u>CM487</u>	SL	LM68149/10	<u>LM12749/10</u>	35.00mm	59.10mm	22.00mm	45.20mm	<u>492015</u>	59.10mm	43.90mm
<u>CM487M</u>	SL MARINE	LM68149/10	<u>LM12749/10</u>	35.00mm	59.10mm	22.00mm	45.20mm	<u>491018</u>	59.10mm	43.90mm
CM485	COMPOSITE	LM67048/10	<u>LM12749/10</u>	31.75mm	59.10mm	22.00mm	45.20mm	<u>491015</u>	59.10mm	37.50mm
CM482	1.5TON	LM29749/10	LM67048/10	38.10mm	65.06mm	31.75mm	59.10mm	<u>493015</u>	69.11mm	52.83mm
<u>CM491</u>	PARALLEL	LM68149/10	LM68149/10	35.00mm	59.10mm	35.00mm	59.10mm	<u>492015</u>	59.10mm	43.90mm
<u>CM491M</u>	PARALLEL MARINE	LM68149/10	LM68149/10	35.00mm	59.10mm	35.00mm	59.10mm	<u>491018</u>	59.10mm	43.90mm
<u>CM492</u>	ALKO 2TON	LM30210J	LM15123/245	50.00mm	89.96mm	31.75mm	61.95mm	<u>64607</u>	89.96mm	60.30mm
<u>CM492M</u>	ALKO 2TON MARINE	<u>LM30210J</u>	LM15123/245	50.00mm	89.96mm	31.75mm	61.95mm	<u>494013</u>	89.96mm	60.30mm
<u>CM494</u>	ALKO 3TON	LM30210J	<u>29749/10</u>	50.00mm	89.96mm	89.96mm	38.10mm	<u>64607</u>	89.96mm	60.30mm
<u>CM494M</u>	ALKO 3TON MARINE	LM30210J	<u>29749/10</u>	50.00mm	89.96mm	89.96mm	38.10mm	<u>494013</u>	89.96mm	60.30mm
<u>CM483</u>	MELB. TR. 1.6TON	LM68149/111	LM44649/10	35.00mm	59.97mm	27.00mm	50.29mm	<u>GS-1719DL</u>	65.22mm	44.00mm
CM484MEL	MELB. TR. 2.0TON	<u>25580/20</u>	<u>67048/10</u>	44.45mm	82.93mm	31.75mm	59.10mm	<u>64190</u>	85mm	50mm
<u>A511</u>	MELB. TR. 2.0TON [MARINE]	<u>25580/20</u>	<u>67048/10</u>	44.45mm	82.93mm	31.75mm	59.10mm	<u>82130</u>	85mm	50mm
<u>CM484</u>	USA DEXTER 2TON	<u>25580/20</u>	<u>15123/245</u>	44.45mm	82.93mm	31.75mm	61.95mm	<u>33940</u>	85.73mm	49.2mm
K71-301-00	USA DEXTER 2TON IMPORT [12"x 2" 8 STUD - 7k LBS]	<u>25580/20</u>	14276/125A	44.45mm	82.93mm	31.75mm	69.01mm	<u>GS-2125</u>	3.376"	2.125"
K71-301-00	USA DEXTER 2TON IMPORT [12"x 2" 8 STUD - 7k LBS]	<u>25580/20</u>	14276/125A	44.45mm	82.93mm	31.75mm	69.01mm	<u>GS-2250</u>	3.376"	2.25"
10VT	VC 2TON	501349/10	<u>68149/10</u>	41.30mm	73.43mm	35.00mm	59.10mm	TC12143	76mm	46mm
TF9	PLLEL	501349/10	501349/10	41.30mm	73.43mm	41.30mm	73.43mm			
PT1129	TROJAN SPECIAL 2TON	48548/10	<u>44649/10</u>	34.925mm	65.08mm	27.00mm	50.29mm	PT10141	65mm	47mm
30205 VENTURE	VENTURE USA	30205J2/Q	30205J2/Q	25.00mm	52.00mm	25.00mm	52.00mm	-	29.97mm	52.07mm
BEAJLM710949-10	ROGERS 6.4TON	710949/10	32210J	65.00mm	105.00mm	50.00mm	89.96mm	JENSPR8379	-	-
BEAC102949-10	ROGERS 4.5TON	102949/10	501349/14	45.24mm	73.43mm	41.27mm	73.43mm	JENS50147	-	-
BEA01349-14	ROGERS 2.25TON	501349/14	501349/14	41.27mm	73.43mm	41.27mm	73.43mm	JENS50167	-	-
<u>A75</u>	SIMPLICITY A75 - 12" DRUM	2788/20	LM67048/10	38.10mm	76.20mm	19.05mm	45.20mm	HAU863	3.00"	1.78"
<u>A75L</u>	SIMPLICITY A75L - 10" DRUM	16150R/2848	LM67048/10	38.10mm	72.23mm	19.05mm	45.20mm	HAU863	3.00"	1.78"
<u>A75H</u>	SIMPLICITY A75H - 4.4TON	26884/23	LM68149/10	42.85mm	76.20mm	35.00mm	59.10mm	HAU862	-	-